



www.alfatronelectronics.com

ALFATRON ELECTRONICS GmbH GERMANY

ALF-TPA33

Audio Extender



All Rights Reserved

Statement

Read this user manual carefully before using the product. Pictures shown in this manual is for reference only, different model and specifications are subject to real product.

This manual is only for operation instruction only, not for any maintenance usage. The functions described in this version are updated till September 2016. In the constant effort to improve our product, we reserve the right to make functions or parameters changes without notice or obligation. Please refer to the dealers for the latest details.

Safety Precaution

To insure the best from the product, please read all instructions carefully before using the device. Save this manual for further reference.

- Follow basic safety precautions to reduce the risk of fire, electrical shock and injury to persons.
- Do not dismantle the housing or modify the module to avoid electrical shock or burn.
- Using supplies or parts not meeting the products' specifications may cause damage, deterioration or malfunction.
- Do not expose the unit to rain, moisture or install this product near water.
- Install the device in a place with fine ventilation.
- Do not twist or pull by force ends of the optical cable. It can cause malfunction.
- Do not use liquid or aerosol cleaners to clean this unit. Always unplug the power to the device before cleaning.
- Unplug the power cord when left unused for a long period of time.
- Refer all servicing to qualified service personnel.

Introduction

This product is an audio extender including Transmitter and Receiver. It is designed to extend the Stereo audio signal up to 170m, and the TOSLINK, COAX audio signal up to 290m via CATx cable.

Features

- Three audio inputs can be switched: TOSLINK/COAX/Stereo.
- Three audio synchronous outputs: TOSLINK, COAX & RCA (L+R).
- The Transmitter is powered by the Receiver 12VDC by PoC technology.
- The transmission distance of Stereo audio signal can up to 170m over a single CATx cable, and the TOSLINK, COAX audio signal up to 290m.


Package List

- 1 x Transmitter
- 1 x Power Adaptor(12VDC,1A)
- 8 x Plastic Cushions
- 1 x Receiver
- 4 x Mounting Ears & 8 x Screws
- 1 x User Manual

Note: If you find any defective or missing parts, please contact your local dealer.


Panel Description

Transmitter



Front Panel	A. TOSLINK digital audio input port, connects to audio source.
	B. COAX digital audio input port, connects to audio source.
	C. Stereo audio input port, connects to audio source.
	D. DIP switcher for selecting audio input source.
Rear Panel	1. Micro USB port for updating firmware.
	2. RJ45 ports, connects to the "TP IN" port of Receiver.
	3. Red power indicator.

Receiver



Front Panel	A.	TOSLINK digital audio output port, connects to audio output device for playing.
	B.	COAX digital audio output port, connects to audio output device for playing.
	C.	RCA (L+R) audio output port, connects to audio output device for playing.
Rear Panel	1.	Micro USB port for updating firmware.
	2.	RJ45 ports, connects to the "TP OUT" port of Transmitter.
	3.	Power port, connects to 12VDC power adaptor.
	4.	Red power indicator.

Specification

Transmitter		Receiver	
Input	TOSLINK, COAX or AUDIO	Input	1 TP IN
Output	1 TP OUT	Output	TOSLINK, COAX & RCA (L+R)
General			
Audio Format	TOSLINK & COAX: PCM/Dobly/DTS; AUDIO: Stereo		
Sound Channel	TOSLINK & COAX: 2.0-7.1		
Frequency Response	20 Hz to 20 kHz, ±3 dB		
Sample Rate	TOSLINK & COAX: 48k/96k/192k 16bit/18bit/24bit		
Transmission Distance	Stereo: Up to 170m (CAT5e/6/7) TOSLINK/COAX: Up to 290m (CAT5e/6/7)		
Power Supply	Input: 100VAC~240VAC, 50/60Hz; Output: 12VDC, 1A		
Power Consumption	2.5W (Max)		
Work Temperature	-10 ~ +55°C		
Humidity	10% ~ 90%		
Net Weight	Transmitter: 110g; Receiver: 119g		
Dimension(W*H*D)	88mm x 80mm x 21.5mm		

Limited warranty in respect of Alfatron Products Only

1.1 This limited warranty covers defects in materials and workmanship in this product.

1.2 Should warranty service be required, proof of purchase must be presented to the Company. The serial number on the product must be clearly visible and not have been tampered with in any way whatsoever.

1.3 This limited warranty does not cover any damage, deterioration or malfunction resulting from any alteration, modification, improper or unreasonable use or maintenance, misuse, abuse, accident, neglect, exposure to excess moisture, fire, improper packing and shipping (such claims must be presented to the carrier), lightning, power surges, or other acts of nature. This limited warranty does not cover any damage, deterioration or malfunction resulting from the installation or removal of this product from any installation, any unauthorized tampering with this product, any repairs attempted by anyone unauthorized by the Company to make such repairs, or any other cause which does not relate directly to a defect in materials and/or workmanship of this product. This limited warranty does not cover equipment enclosures, cables or accessories used in conjunction with this product.

This limited warranty does not cover the cost of normal maintenance. Failure of the product due to insufficient or improper maintenance is not covered.

1.4 The Company does not warrant that the product covered hereby, including, without limitation, the technology and/or integrated circuit(s) included in the product, will not become obsolete or that such items are or will remain compatible with any other product or technology with which the product may be used.

1.5 Only the original purchaser of this product is covered under this limited warranty. This limited warranty is not transferable to subsequent purchasers or owners of this product.

1.6 Unless otherwise specified, the goods are warranted in accordance with the manufacturer's product specific warranties against any defect attributable to faulty workmanship or materials, fair wear and tear being excluded.

1.7 This limited warranty only covers the cost of faulty goods and does not include the cost of labor and travel to return the goods to the Company's premises.

1.8 In the event of any improper maintenance, repair or service being carried out by any third persons during the warranty period without the Company's written authorization, the limited warranty shall be void.

1.9 A 7 (seven) year limited warranty is given on the aforesaid product where used correctly according to the Company's instructions, and only with the use of the Company's components.

1.10 The Company will, at its sole option, provide one of the following three remedies to whatever extent it shall deem necessary to satisfy a proper claim under this limited warranty:

1.10.1 Elect to repair or facilitate the repair of any defective parts within a reasonable period of time, free of any charge for the necessary parts and labor to complete the repair and restore this product to its proper operating condition.; or

1.10.2 Replace this product with a direct replacement or with a similar product deemed by the Company to perform substantially the same function as the original product; or

1.10.3 Issue a refund of the original purchase price less depreciation to be determined based on the age of the product at the time remedy is sought under this limited warranty.

1.11 The Company is not obligated to provide the Customer with a substitute unit during the limited warranty period or at any time thereafter.

1.12 If this product is returned to the Company this product must be insured during shipment, with the insurance and shipping charges prepaid by the Customer. If this product is returned uninsured, the Customer assumes all risks of loss or damage during shipment. The Company will not be responsible for any costs related to the removal or re-installation of this product from or into any installation. The Company will not be responsible for any costs related to any setting up this product, any adjustment of user controls or any programming required for a specific installation of this product.

1.13 Please be aware that the Company's products and components have not been tested with competitor's products and therefore the Company cannot warrant products and/or components used in conjunction with competitor's products.

1.14 The appropriateness of the goods for the purpose intended is only warranted to the extent that the goods are used in accordance with the Company's installation, classification and usage instructions.

1.15 Any claim by the Customer which is based on any defect in the quality or condition of the goods or their failure to correspond with specification shall be notified in writing to the Company within 7 days of delivery or (where the defect or failure was not apparent on reasonable inspection by the Customer) within a reasonable time after discovery of the defect or failure, but, in any event, within 6 months of delivery.

1.16 If delivery is not refused, and the Customer does not notify the Company accordingly, the Customer may not reject the goods and the Company shall have no liability and the Customer shall pay the price as if the goods had been delivered in accordance with the Agreement.

1.17 THE MAXIMUM LIABILITY OF THE COMPANY UNDER THIS LIMITED WARRANTY SHALL NOT EXCEED THE ACTUAL PURCHASE PRICE PAID FOR THE PRODUCT